

WRT



SPECIFICATIONS

Voltage: 24V only

Capacity (at 24" Load center): 4000-6000

Standard Battery (weight, lbs.): 510 AH (1050)

Standard Charger (weight, lbs.): 75 AH (60)

Speed Control: Transistor Speed Control

Standard Drive Wheels: Poly 10.5" x 5"

Standard Load Wheels: Dual Poly 3.5" x 2 5/8"

Stability Casters: Standard 3.25" x 2.75"

Fork Length (nominal): 48"

Standard Fork OD: 27"

Fork Height Raised: 9 1/8"

Fork Height Lowered: 3.25"

Travel Speed (mph):

Empty: 6.5

Loaded: 4.8

Grade Clearance Raised: 40%

Gradeability Empty: 15%

Gradeability Loaded: 10%

Right Angle Stacking w/ 40"W x 48"L Pallet:

Aisle*# : 86"

Bay*# : 42"

Weight (lbs.): 1130***

* Based on standard battery compartment

6"-12" should be added for ease of operation

*** Without battery

WRT-60 24 Volt

WRT-60 6,000 Lbs @ 24" Load Center 27" x 48" Forks 24V Walkie/Rider

WRT-40 24 Volt

WRT-40 4,000 Lbs @ 24" Load Center 27" x 48" Forks 24V Walkie/Rider

